

# MX-A55Ni1


80%Ar - 20%CO<sub>2</sub> EN ISO 17632-A-T 46 6 Mn1Ni M M 3 H5 AWS A5.28 E80C-G EN ISO 9606-1: FM1 EN ISO 4063: 138


## **Description and Application**

MX-A55Ni1 is a metal cored wire, which has been specially formulated to meet the rigorous demands for low temperature service steels.

MX-A55Ni1 fulfills the NACE requirements for oil and gas production equipment in sour gas service and these properties make for a varied range of usages in pipeline construction, offshore applications and pressure vessels.

#### **Recommended Parameter Range, for flat position**





### Typical Chemical Analysis (wt. %)

С	Si	Mn	Р	S	Ni	Cr	Mo
0.05	0.34	1.67	0.007	0.008	0.86	-	-

#### **Typical Mechanical Properties**

	R <sub>e</sub> (MPa)	R <sub>m</sub> (MPa)	A <sub>5</sub> (%)	CV(J)-60°C
	542	607	29	123
Guaranty	min.460	530~680	min.20	min.47

Example of Diffusible hydrogen content: 2.5 [ml/100g]

## **Welding Positions**



#### **Approvals**

LR	DNV GL	BV	ABS	R.M.R.S	Others
-	-	-	-	-	CE