

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **DW-310**
Unique formula identifier (UFI) K830-00FA-3001-UQ9U

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Welding and soldering product
The product is intended for professional use
Specific process or activity welding (welding process)

1.3 Details of the supplier of the safety data sheet

Kobelco Welding of Europe B.V.
Eisterweg 8
6422 PN Heerlen
Netherlands

Telephone: +31(0)45-5471111
Telefax: e-mail: info@kobelcowelding.nl

e-mail (competent person) info@kobelcowelding.nl

1.4 Emergency telephone number

Emergency information service +31(0)45-5471111
This number is only available during the following office hours: Mon-Fri 09:00 - 17:00

Poison centre		
Country	Name	Telephone
United Kingdom	National Poisons Information Service (NPIS)	0344-8920111 (medical professionals only)
United Kingdom	NHS (general public)	non-emergency: 111 or a doctor; emergency: 999

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.4S	skin sensitisation	1	Skin Sens. 1	H317
3.6	carcinogenicity	2	Carc. 2	H351
3.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372

For full text of H-phrases: see SECTION 16

Code	Supplemental hazard information
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

2.2 Label elements

Labelling

- signal word Danger

- pictograms

GHS07, GHS08



- hazard statements

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H372 Causes damage to organs through prolonged or repeated exposure.

- precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- supplemental hazard information

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

- hazardous ingredients for labelling

Contains: nickel powder.

2.3 Other hazards

Avoid breathing dust. Avoid contact with eyes. Avoid skin contact.

When this product is used in a welding process, the most significant hazards are electric shock, fumes, gases, radiation, spatter, slag and heat.

Shock: electric shock can kill.

Fumes: Overexposure to welding fumes may result in symptoms like dizziness, nausea, dryness or irritation of the nose, throat or eyes. Chronic overexposure to welding fumes may affect pulmonary function.

Gases: gases may cause gas poisoning.

Radiation: arc rays can severely damage eyes or skin.

Spatter, slag and heat: spatter and slag can damage eyes. Spatter, slag, melting material, arc rays and hot welds can cause burn injuries and start fires.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Chromium	CAS No 7440-47-3 EC No 231-157-5 REACH Reg. No 01-2119485652- 31-xxxx	20 – 30			IOELV
Nickel	CAS No 7440-02-0 EC No 231-111-4 Index No 028-002-01-4 REACH Reg. No 01-2119438727- 29-xxxx	13 – 23	Skin Sens. 1 / H317 Carc. 2 / H351 STOT RE 1 / H372 Aquatic Chronic 3 / H412		GHS-HC
Manganese	CAS No 7439-96-5 EC No 231-105-1 REACH Reg. No 01-2119449803- 34-xxxx	< 5			IOELV
Copper	CAS No 7440-50-8 EC No 231-159-6 Index No 029-024-00-X REACH Reg. No 01-2119480154- 42-xxxx	< 1	Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411		GHS-HC
calcium oxide	CAS No 1305-78-8 EC No 215-138-9 REACH Reg. No 01-2119475325- 36-xxxx 01-2119666323- 39-xxxx 01-2119862019- 36-xxxx 01-2119976279- 19-xxxx 01-2120034600- 72-xxxx	< 1	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335		IOELV

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Sodium fluoride	CAS No 7681-49-4 EC No 231-667-8 Index No 009-004-00-7 REACH Reg. No 01-2119539420- 47-xxxx	< 1	Acute Tox. 3 / H301 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 EUH032		GHS-HC IOELV

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)
IOELV: Substance with a community indicative occupational exposure limit value

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
sodium fluoride	CAS No 7681-49-4 EC No 231-667-8	-	-	148.5 mg/kg	oral

Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Disconnect and turn off the power. If the victim is semi- or unconscious, open the airway. If the victim cannot breathe, give artificial respiration. If there is no pulse, massage the chest and apply artificial respiration.

Electrical shock

Disconnect and turn off the power. If the victim is semi- or unconscious, open the airway. If the victim cannot breathe, give artificial respiration. If there is no pulse, massage the chest and apply artificial respiration.

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. If experiencing respiratory symptoms: Call a doctor.

Following skin contact

Brush off loose particles from skin. Rinse skin with water/shower. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

Following eye contact

Do not rub the eyes. Mechanical stress can cause damage to the cornea. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a POISON CENTER or doctor if you feel unwell.

DW-310Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Alcohol resistant foam, Dry extinguishing powder, Carbon dioxide (CO₂), Water spray**5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

Hazardous combustion products

During fire hazardous fumes/smoke could be produced.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Take up mechanically.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from fire.

Recommendations

- measures to prevent fire as well as aerosol and dust generation
- No special measures are necessary.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- explosive atmospheres
Removal of dust deposits.
- flammability hazards
Keep away from fire. Keep away from combustible material.
- incompatible substances or mixtures
Acids, Alkalis, Oxidisers

Control of effects

Protect against external exposure, such as

High temperatures, Humidity

Consideration of other advice

Store in a well-ventilated place. Keep container tightly closed.

- general rule

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside a wall. Keep welding consumables away from chemical substances like acids which could cause chemical reactions.

- ventilation requirements
Use local and general ventilation.
- packaging compatibilities
Keep only in original container.

7.3 Specific end use(s)

Welding (welding process).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Notation	Source
EU	calcium oxide	1305-78-8	IOELV		1		4	r	2017/164/EU

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Notation	Source
EU	manganese	7439-96-5	IOELV		0.2			i	2017/164/EU
EU	manganese	7439-96-5	IOELV		0.05			r	2017/164/EU
EU	chromium	7440-47-3	IOELV		2				2006/15/EC
EU	fluorine, inorganic compounds	7681-49-4	IOELV		2.5				2000/39/EC
GB	dust		WEL		10			i	EH40/2005
GB	dust		WEL		4			r	EH40/2005
GB	calcium oxide	1305-78-8	WEL		2				EH40/2005
GB	calcium oxide	1305-78-8	WEL		1		4	r	EH40/2005
GB	titanium dioxide	13463-67-7	WEL		10			i	EH40/2005
GB	titanium dioxide	13463-67-7	WEL		4			r	EH40/2005
GB	manganese	7439-96-5	WEL		0.2			i	EH40/2005
GB	manganese	7439-96-5	WEL		0.05			r	EH40/2005
GB	nickel	7440-02-0	WEL		0.1				EH40/2005
GB	chromium	7440-47-3	WEL		0.5				EH40/2005
GB	copper	7440-50-8	WEL		1		2	dm	EH40/2005
GB	copper	7440-50-8	WEL		0.2			fume	EH40/2005
GB	fluorides, inorganic	7681-49-4	WEL		2.5			F	EH40/2005

Notation

dm as dusts and mists
 F calculated as F (fluorine)
 fume as fume
 i inhalable fraction
 r respirable fraction
 STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
 TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
chromium	7440-47-3	DNEL	0.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
nickel powder	7440-02-0	DNEL	0.05 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
nickel powder	7440-02-0	DNEL	0.05 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

DW-310

 Version number: 3.0
 Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
nickel powder	7440-02-0	DNEL	0.05 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
nickel powder	7440-02-0	DNEL	11.9 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Manganese	7439-96-5	DNEL	0.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Manganese	7439-96-5	DNEL	0.004 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sodium fluoride	7681-49-4	DNEL	2.5 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
sodium fluoride	7681-49-4	DNEL	2.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
sodium fluoride	7681-49-4	DNEL	0.36 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sodium fluoride	7681-49-4	DNEL	0.36 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
calcium oxide	1305-78-8	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
calcium oxide	1305-78-8	DNEL	4 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
granulated copper	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
granulated copper	7440-50-8	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
granulated copper	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
granulated copper	7440-50-8	DNEL	137 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
granulated copper	7440-50-8	DNEL	273 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
chromium	7440-47-3	PNEC	6.5 µg/l	aquatic organisms	freshwater	short-term (single instance)
chromium	7440-47-3	PNEC	205.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
chromium	7440-47-3	PNEC	21.1 mg/kg	terrestrial organisms	soil	short-term (single instance)
nickel powder	7440-02-0	PNEC	7.1 µg/l	aquatic organisms	freshwater	short-term (single instance)
nickel powder	7440-02-0	PNEC	8.6 µg/l	aquatic organisms	marine water	short-term (single instance)
nickel powder	7440-02-0	PNEC	0.33 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

DW-310

 Version number: 3.0
 Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
nickel powder	7440-02-0	PNEC	109 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
nickel powder	7440-02-0	PNEC	109 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
nickel powder	7440-02-0	PNEC	29.9 mg/kg	terrestrial organisms	soil	short-term (single instance)
Manganese	7439-96-5	PNEC	0.028 mg/l	aquatic organisms	water	intermittent release
Manganese	7439-96-5	PNEC	0.034 mg/l	aquatic organisms	freshwater	short-term (single instance)
Manganese	7439-96-5	PNEC	0.003 mg/l	aquatic organisms	marine water	short-term (single instance)
Manganese	7439-96-5	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Manganese	7439-96-5	PNEC	3.3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Manganese	7439-96-5	PNEC	0.34 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Manganese	7439-96-5	PNEC	3.4 mg/kg	terrestrial organisms	soil	short-term (single instance)
sodium fluoride	7681-49-4	PNEC	0.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
sodium fluoride	7681-49-4	PNEC	51 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium fluoride	7681-49-4	PNEC	11 mg/kg	terrestrial organisms	soil	short-term (single instance)
calcium oxide	1305-78-8	PNEC	0.37 mg/l	aquatic organisms	water	intermittent release
calcium oxide	1305-78-8	PNEC	0.37 mg/l	aquatic organisms	freshwater	short-term (single instance)
calcium oxide	1305-78-8	PNEC	0.24 mg/l	aquatic organisms	marine water	short-term (single instance)
calcium oxide	1305-78-8	PNEC	2.27 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
calcium oxide	1305-78-8	PNEC	817.4 mg/kg	terrestrial organisms	soil	short-term (single instance)
granulated copper	7440-50-8	PNEC	6.3 µg/l	aquatic organisms	freshwater	short-term (single instance)
granulated copper	7440-50-8	PNEC	5.2 µg/l	aquatic organisms	marine water	short-term (single instance)
granulated copper	7440-50-8	PNEC	230 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
granulated copper	7440-50-8	PNEC	87 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
granulated copper	7440-50-8	PNEC	676 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
granulated copper	7440-50-8	PNEC	65 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases below the TLVs in the worker's breathing zone and the general area. Use extra ventilation when welding galvanized plate or coated plate.

Individual protection measures (personal protective equipment)

Eye/face protection



Wear helmet or use face shield with filter lens. As a rule of thumb, start with a shade which is too dark to see the weld zone. Then go to the next lighter shade which gives sufficient view of the weld zone. Provide protective screens and flash goggles, if necessary, to shield others.

Skin protection



Chemical protective clothing.

Hand protection



Welding gloves according to EN12477:2001 and A1:2005 in case of arc welding. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The exact break through time should be requested at the protective glove manufacturer and must be observed.

- type of material

Nitrile rubber

- material thickness

Use gloves with a minimum material thickness: $\geq 0,38$ mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures



Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling. Wear head, hand and body protection which help to prevent injury from radiation, sparks and electric shock. At a minimum this includes welder's gloves and protective face shield and may include arm protectors, aprons, hats, shoulder protection as well as dark substantial clothing.

Train the welder not to touch live electrical parts and to insulate himself from work and ground.

Ear protection



Wear earplugs or earmuffs when using engine driven arc welding machine or pulsed arc welding machine that generates high-level noise.

Respiratory protection



Use respirable fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below TLV. Keep head out of the fumes and gases.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	solid (electrode)
Colour	grey
Odour	odourless
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	LEL: 0 vol% / UEL: 0 vol% calculated value, referring to a component of the mixture
Flash point	not applicable
Auto-ignition temperature	information on this property is not available
Decomposition temperature	no data available
pH (value)	not applicable
Kinematic viscosity	not relevant
Solubility	not determined

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	not determined
-----------------	----------------

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	no data available
--------------------------	-------------------

9.2 Other information

There is no additional information.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	
Temperature class	T2 (maximum permissible surface temperature on the equipment: 300 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Contact with chemical substances could cause generation of gas.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Reacts with: Acids. Alkalis. Oxidising substances.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers, Acids, Alkalis

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous decomposition products includes those from the volatilization, reaction or oxidation of the material listed in section 3 and those from the base metal and coating. Manganese has a low exposure limit, in some countries, that may be easily exceeded. Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Reasonably expected fume constituents of this product would include oxides of metals

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Inhalation of welding fumes and gases can be dangerous to your health. The composition and quantity of both are dependent upon the material being worked, the process, procedures and consumables used.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Overexposure to gases, fumes and dusts may include irritation of the eyes, lungs, nose and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing or chest pain. Exposure to the fluoride ion may cause hypocalcaemia-calcium deficiency in the blood that can result in muscle cramps and inflammation and necrosis of mucous membranes.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
sodium fluoride	7681-49-4	oral	148.5 mg/kg

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Chromium	7440-47-3	inhalation: dust/ mist	LC50	>5.41 mg/l/4h	rat
Nickel	7440-02-0	oral	LD50	>9,000 mg/kg	rat
Manganese	7439-96-5	oral	LD50	>2,000 mg/kg	rat
Manganese	7439-96-5	inhalation: dust/ mist	LC50	>5.14 mg/l/4h	rat
Sodium fluoride	7681-49-4	oral	LD50	148.5 mg/kg	rat
calcium oxide	1305-78-8	oral	LD50	>2,000 mg/kg	rat
calcium oxide	1305-78-8	inhalation: dust/ mist	LC50	>6.04 mg/l/4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans						
Name of substance	CAS No	Wt%	Classification	Remarks	Number	Date indication
DW-310		100	1			2018
nickel powder	7440-02-0	15	2B			1990
chromium	7440-47-3	20	3			1990

Legend

- 1 Carcinogenic to humans
- 2B Possibly carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Summary of evaluation of the CMR properties

Nickel is considered carcinogenic. Long term overexposure to nickel fumes may also cause pulmonary fibrosis and oedema. Welding fumes (not otherwise specified) are possibly carcinogenic to humans.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Nickel is considered carcinogenic. Long term overexposure to nickel fumes may also cause pulmonary fibrosis and oedema. Overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest X-rays. The severity of the change is proportional to the length of the exposure. The changes may be caused by non-work factors such as smoking, etc. Long term exposure to welding and allied processes gasses, dusts and fumes may contribute to pulmonary irritation or pneumoconiosis. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances and spastic gait. The effect of manganese on the nervous system is irreversible. Inhalation of too much iron oxide fume over a long time can cause siderosis, sometimes called "iron pigmentation" of the lung, which can be seen on a chest x-ray but causes little or no disability. Chronic overexposure to iron (>50-100 mg Fe per day) can result in pathological deposition of iron in body tissues of which are fibrosis of the pancreas, diabetes mellitus and liver cirrhosis. Chronic fluoride absorption can result in osseous fluorosis, increased radiographic density of the bones and mottling of the teeth. Chromium (in some forms) is considered carcinogenic. Chromium compounds have a corrosive action on the skin and mucous membranes and forms lesions on exposed skin and the nasal septum. Liver damage and allergic skin rash have also been reported. Overexposure to copper fumes may lead to copper poisoning, resulting in hemolytic anemia and liver, kidney and spleen damage.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.

Other information

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
chromium	7440-47-3	EC50	$\leq 18.9 \text{ mg/l}$	aquatic invertebrates	48 h
nickel powder	7440-02-0	LC50	15.3 mg/l	fish	96 h
nickel powder	7440-02-0	EC50	$406 \text{ } \mu\text{g/l}$	aquatic invertebrates	24 h
nickel powder	7440-02-0	ErC50	$237 \text{ } \mu\text{g/l}$	algae	72 h
nickel powder	7440-02-0	NOEC	0.5 mg/l	aquatic invertebrates	72 h
nickel powder	7440-02-0	LOEC	$>4,407 \text{ } \mu\text{g/l}$	aquatic invertebrates	48 h
nickel powder	7440-02-0	growth (EbCx) 10%	$662.6 \text{ } \mu\text{g/l}$	aquatic invertebrates	48 h
nickel powder	7440-02-0	growth rate (Er-Cx) 10%	$18.3 \text{ } \mu\text{g/l}$	algae	72 h
Manganese	7439-96-5	LC50	$>3.6 \text{ mg/l}$	fish	96 h
Manganese	7439-96-5	EC50	$>1.6 \text{ mg/l}$	aquatic invertebrates	48 h
Manganese	7439-96-5	ErC50	4.5 mg/l	algae	72 h
Manganese	7439-96-5	NOEC	3.6 mg/l	fish	96 h
Manganese	7439-96-5	LOEC	5.3 mg/l	algae	72 h

DW-310

 Version number: 3.0
 Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Manganese	7439-96-5	growth rate (Er-Cx) 10%	3.4 mg/l	algae	72 h
Manganese	7439-96-5	growth (EbCx) 10%	2.6 mg/l	algae	72 h
sodium fluoride	7681-49-4	EC50	48 mg/l	aquatic invertebrates	96 h
sodium fluoride	7681-49-4	NOEC	83 mg/l	microorganisms	48 h
calcium oxide	1305-78-8	LC50	50.6 mg/l	fish	96 h
calcium oxide	1305-78-8	EC50	49.1 mg/l	aquatic invertebrates	48 h
calcium oxide	1305-78-8	ErC50	184.6 mg/l	algae	72 h
calcium oxide	1305-78-8	NOEC	33.3 mg/l	aquatic invertebrates	48 h
calcium oxide	1305-78-8	LOEC	80 mg/l	algae	72 h
calcium oxide	1305-78-8	growth rate (Er-Cx) 10%	79.22 mg/l	algae	72 h
granulated copper	7440-50-8	LC50	193 µg/l	fish	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
nickel powder	7440-02-0	ErC50	8,363 µg/l	fish	40 d
nickel powder	7440-02-0	LC50	≤144 µg/l	aquatic invertebrates	21 d
nickel powder	7440-02-0	EC50	≤108 µg/l	aquatic invertebrates	21 d
nickel powder	7440-02-0	EbC50	6.2 µg/l	aquatic invertebrates	30 d
nickel powder	7440-02-0	NOEC	0.057 mg/l	fish	32 d
nickel powder	7440-02-0	LOEC	0.12 mg/l	fish	32 d
nickel powder	7440-02-0	growth (EbCx) 10%	404.3 µg/l	aquatic invertebrates	10 d
Manganese	7439-96-5	LC50	<15.61 mg/l	fish	28 d
Manganese	7439-96-5	EC50	19.5 mg/l	aquatic invertebrates	21 d
Manganese	7439-96-5	NOEC	1.7 mg/l	aquatic invertebrates	8 d
Manganese	7439-96-5	growth (EbCx) 20%	<1.1 mg/l	aquatic invertebrates	21 d
sodium fluoride	7681-49-4	NOEC	4 mg/l	fish	21 d
calcium oxide	1305-78-8	LC50	53.1 mg/l	aquatic invertebrates	14 d
calcium oxide	1305-78-8	EC50	300.4 mg/l	microorganisms	3 h
calcium oxide	1305-78-8	NOEC	32 mg/l	aquatic invertebrates	14 d

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
calcium oxide	1305-78-8	growth (EbCx) 20%	229.2 mg/l	microorganisms	3 h
granulated copper	7440-50-8	NOEC	11.4 µg/l	fish	45 d

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

Not mobile.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number	not subject to transport regulations
14.2 UN proper shipping name	not relevant
14.3 Transport hazard class(es)	none
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	There is no additional information.
14.7 Maritime transport in bulk according to IMO instruments	No data available.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Additional information for each of the UN Model Regulations

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet is purely informative and does comply with EU regulations, but not with country-specific regulations.

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name acc. to inventory	CAS No	Remarks	Threshold for releases to air (kg/year)
copper	7440-50-8	(8)	100
nickel	7440-02-0	(8)	50
chromium	7440-47-3	(8)	100

Legend

(8) All metals shall be reported as the total mass of the element in all chemical forms present in the release

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
granulated copper	Metals and their compounds		a)	
nickel powder	nickel	7440-02-0	b)	
nickel powder	nickel compounds		b)	
nickel powder	nickel compounds	7440-02-0	c)	
nickel powder	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
nickel powder	Metals and their compounds		a)	
calcium oxide	Metals and their compounds		a)	
chromium	Metals and their compounds		a)	
Manganese	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
Manganese	Metals and their compounds		a)	
sodium fluoride	Metals and their compounds		a)	

Legend

- a) Indicative list of the main pollutants
- b) List of priority substances in the field of water policy
- c) Environmental Quality Standards for Priority Substances and certain other pollutants

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

None of the ingredients are listed.

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name	Name acc. to inventory	Conditions of restriction	No
nickel powder	Nickel	R27	27

Legend

R27

1. Shall not be used:
 - (a) in any post assemblies which are inserted into pierced ears and other pierced parts of the human body unless the rate of nickel release from such post assemblies is less than 0.2 µg/cm²/week (migration limit);
 - (b) in articles intended to come into direct and prolonged contact with the skin such as:
 - earrings,
 - necklaces, bracelets and chains, anklets, finger rings,
 - wrist-watch cases, watch straps and tighteners,
 - rivet buttons, tighteners, rivets, zippers and metal marks, when these are used in garments,
 If the rate of nickel release from the parts of these articles coming into direct and prolonged contact with the skin is greater than 0.5 µg/cm²/week.
 - (c) in articles referred to in point (b) where these have a non-nickel coating unless such coating is sufficient to ensure that the rate of nickel release from those parts of such articles coming into direct and prolonged contact with the skin will not exceed 0.5 µg/cm²/week for a period of at least two years of normal use of the article.
2. Articles which are the subject of paragraph 1 shall not be placed on the market unless they conform to the requirements set out in that paragraph.
3. The standards adopted by the European Committee for Standardisation (CEN) shall be used as the test methods for demonstrating the conformity of articles to paragraphs 1 and 2.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this mixture.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Complete revised version.

Section	Former entry (text/value)	Actual entry (text/value)
1.1	Trade name: DW-310 (electrodes for flux cored arc welding)	
1.1	Registration number (REACH): not relevant (mixture)	
1.1		Trade name: DW-310
1.1		Unique formula identifier (UFI): K830-00FA-3001-UQ9U
1.3	Details of the supplier of the safety data sheet: Kobelco Welding of Europe B.V. Eisterweg 8 6422 PN Heerlen Netherlands Telephone: +31(0)45-5471111 Telefax: +31(0)45-5471100 e-mail: info@kobelcowelding.nl	Details of the supplier of the safety data sheet: Kobelco Welding of Europe B.V. Eisterweg 8 6422 PN Heerlen Netherlands Telephone: +31(0)45-5471111 Telefax: e-mail: info@kobelcowelding.nl
1.4		Poison centre: change in the listing (table)
2.1		Classification acc. to GHS: change in the listing (table)
2.1		Classification acc. to GHS: change in the listing (table)
2.1	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. Spillage and fire water can cause pollution of watercourses.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure.
2.2		- pictograms: change in the listing (table)
2.2		- hazard statements: change in the listing (table)
2.2		- precautionary statements: change in the listing (table)
2.2		- supplemental hazard information: change in the listing (table)
2.2	- hazardous ingredients for labelling: nickel powder (particle diameter < 1mm), calcium oxide	- hazardous ingredients for labelling: Contains: nickel powder.
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0,1%.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Section	Former entry (text/value)	Actual entry (text/value)
3.2	Mixtures: The product does not contain any (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the substance and hence require reporting in this section.	Mixtures: The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.
3.2		Mixtures: change in the listing (table)
3.2		Mixtures: change in the listing (table)
3.2	Remarks: For full text of H-phrases: see SECTION 16. All the percentages given are percentages by weight unless stated otherwise.	Remarks: All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.
4.1	Following inhalation: Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. If experiencing respiratory symptoms: Call a doctor.	Following inhalation: Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. If experiencing respiratory symptoms: Call a doctor.
4.1	Following skin contact: Brush off loose particles from skin. Rinse skin with water/shower.	Following skin contact: Brush off loose particles from skin. Rinse skin with water/shower. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
4.1	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart.	Following eye contact: Do not rub the eyes. Mechanical stress can cause damage to the cornea. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
4.1	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell.	Following ingestion: Rinse mouth with water (only if the person is conscious). Call a POISON CENTER or doctor if you feel unwell.
4.3	Indication of any immediate medical attention and special treatment needed: For specialist advice physicians should contact the anti poison control centre.	Indication of any immediate medical attention and special treatment needed: For specialist advice physicians should contact the poison centre.
5.3	Special protective equipment for firefighters: Self-contained breathing apparatus (EN 133). Standard protective clothing for firefighters.	Special protective equipment for firefighters: Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.
6.3	Advices on how to contain a spill: Covering of drains. Take up mechanically.	Advice on how to contain a spill: Covering of drains.
7.2		- packaging compatibilities: Keep only in original container.
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)
8.1		Relevant DNELs of components of the mixture: change in the listing (table)
8.1		Relevant PNECs of components: change in the listing (table)
8.2	Skin protection: Protective clothing (EN 340).	Skin protection: wear protective clothing Chemical protective clothing.

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Section	Former entry (text/value)	Actual entry (text/value)
8.2	Hand protection: safety gloves must be worn Welding gloves according to EN12477:2001 and A1:2005 in case of arc welding. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The exact break through time should be requested at the protective glove manufacturer and must be observed.	Hand protection: safety gloves must be worn Welding gloves according to EN12477:2001 and A1:2005 in case of arc welding. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The exact break through time should be requested at the protective glove manufacturer and must be observed.
8.2		Type of material: Nitrile rubber
8.2		Material thickness: Use gloves with a minimum material thickness: $\geq 0,38$ mm.
8.2	Breakthrough times of the glove material: >480 minutes (permeation: level 6).	Breakthrough time of the glove material: Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).
8.2	Environmental exposure controls: Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.	Environmental exposure controls: Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.
9.1	Appearance	
9.1	Other safety parameters	
9.1	Flammability (solid, gas): non-combustible	Flammability: this material is combustible, but will not ignite readily
9.1		Lower and upper explosion limit: LEL: 0 vol% / UEL: 0 vol% calculated value, referring to a component of the mixture
9.1	Evaporation rate: not determined	
9.1	Explosion limits of dust clouds: not determined	
9.1		Decomposition temperature: no data available
9.1		Kinematic viscosity: not relevant
9.1	Vapour pressure: 0 Pa at 25 °C	Vapour pressure: not determined
9.1		Density and/or relative density
9.1	Vapour density: this information is not available	
9.1	Partition coefficient	
9.1	Viscosity: not relevant (solid matter)	
9.1	Explosive properties: none	
9.1	Oxidising properties: none	

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Section	Former entry (text/value)	Actual entry (text/value)
9.1		Particle characteristics: no data available
9.2	Other information: Of no significance.	Other information: There is no additional information.
9.2		Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant
9.2		Other safety characteristics
9.2		Temperature class: T2 (maximum permissible surface temperature on the equipment: 300 °C)
10.2	Chemical stability: See below "Conditions to avoid".	Chemical stability: The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
10.4	Conditions to avoid: Keep away from heat.	Conditions to avoid: There are no specific conditions known which have to be avoided.
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)
11.1		Acute toxicity of components: change in the listing (table)
11.1	Skin corrosion/irritation: Causes skin irritation.	Skin corrosion/irritation: Shall not be classified as corrosive/irritant to skin.
11.1	Serious eye damage/eye irritation: Causes serious eye damage.	Serious eye damage/eye irritation: Shall not be classified as seriously damaging to the eye or eye irritant.
11.1		IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: change in the listing (table)
11.2		Information on other hazards
11.2		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.
11.2		Other information: There is no additional information.
12.1	Toxicity: Harmful to aquatic life with long lasting effects.	Toxicity: Shall not be classified as hazardous to the aquatic environment.
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)
12.6	Endocrine disrupting potential: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.
14.3	Transport hazard class(es)	Transport hazard class(es): none

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Section	Former entry (text/value)	Actual entry (text/value)
14.3	Class: -	
14.4	Packing group: not relevant	Packing group: not assigned
14.7	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN): Not subject to ADR, RID and ADN.	
15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	Safety, health and environmental regulations/legislation specific for the substance or mixture: This Safety Data Sheet is purely informative and does comply with EU regulations, but not with country-specific regulations.
15.1	Restrictions according to REACH, Annex XVII	
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)
15.1	List of substances subject to authorisation (REACH, Annex XIV): None of the ingredients are listed.	
15.1		Seveso Directive
15.1		2012/18/EU (Seveso III): change in the listing (table)
15.1		Pollutant release and transfer registers (PRTR): change in the listing (table)
15.1		List of pollutants (WFD): change in the listing (table)
15.1		Regulation on persistent organic pollutants (POP): None of the ingredients are listed.
15.1		National regulations (GB)
15.1		List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list: None of the ingredients are listed.
15.1		Restrictions according to GB REACH, Annex 17
15.1		Dangerous substances with restrictions (GB REACH, Annex 17): change in the listing (table)
16		Abbreviations and acronyms: change in the listing (table)
16	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU. Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	Key literature references and sources for data: Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)

DW-310

 Version number: 3.0
 Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
2017/164/EU	Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EbC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

Abbr.	Descriptions of used abbreviations
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LOEC	Lowest Observed Effect Concentration
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

DW-310

Version number: 3.0
Replaces version of: 2012-04-19 (1)

Revision: 2023-11-22

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H301	Toxic if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Warning text on the label

WARNING: PROTECT yourself and others. Read and understand this information.

FUMES AND GASES can be hazardous to your health.

ARC RAYS can injure eyes and burn skin.

ELECTRIC SHOCK can KILL.

- Before use, read and understand the manufacturer's instructions, Material Safety Data Sheets (MSDSs), and your employer's safety practices.
- Keep your head out of the fumes.
- Use adequate ventilation, exhaust at the arc, or both, to keep fumes and gases from your breathing zone and the general area.
- Wear correct eye, ear, and body protection.
- Do not touch free electrical parts.